



HOUSING **IMPELLER** BEARING TERMINATION OPERATING TEMPERATURE INSULATION RESISTANCE DIELECTRIC STRENGTH WEIGHT ROHS COMPLIANCE MOTOR TYPE ADDITIONAL FUNCTION

Steel Steel
Aluminum
Ball
Lead Wire
0°C to + 45°C
10M Ohms Min.@500VDC
3mA Max. at 1500VAC for 1 second
1400g
Yes Yes Shaded Pole Motor


APPLICATION


1. FACTORY

ESPECIALLY FOR THE ACTION TO THE STATE OF TH

2. HOUSE AND COTTAGE
House, Apartment building, Cottage, etc.
3. Ventilation, Air conditioning, Dryer, Dehumidifier, etc.

DIMENSION





SPECIFICATION

MODEL NO.	RATED VOLTAGE (V)	FREQUENCY (Hz)	RATED CURRENT (A)	INPUT POWER (W)	SPEED (RPM)	MAX. AIR F	PRESSURE mmH ₂ O	MAX.	AIR FLOW m³/min	NOISE dB(A) @1M
AB13280V2HB	230	50/60	0.4/0.5	45/47	2650/3100	0.62/0.90	16/23	61/67	1.72/1.89	

AIR PERFORMANCE

