

SEP0402EC SERIES

High Current SMD Power Inductors



RoHS Compliant

PART NUMBERING SYSTEM


<u>SEP</u>	<u>0402EC</u>	—	<u>1R0M</u>	—	<u>LF</u>
TYPE	DIMENSIONS		INDUCTANCE		LEAD FREE

FEATURES :

- Low profile (2.0mm max. height) and 4.6 mm max. square.
- Magnetically shielded and low DC resistance and Suitable for large current .
- Ultra low buzz noise, due to composite construction .
- Ideal for DC – DC converter inductor application in hand help personal Computer ,etc .
- Frequency range up to 1.0 MHz .
- Large current handling capability .

SHAPES AND DIMENSIONS :


UNIT : mm



A=5.0 Max. B=4.4 Max. C=0.8±0.3 D=2.1 Max. E=1.5±0.3

RECOMMENDED PATTERNS

UNIT : mm



H=2.5 G= 2.2 I = 5.2

SEP0402EC SERIES

High Current SMD Power Inductors




RoHS Compliant

SPECIFICATION TABLE

PART NUMBER	INDUCTANCE (μ H)	Isat (A) (Typ.)	Irms (A) (Typ.)	DCR (m Ω) (Typ.)	DCR (m Ω) (Max.)	TEST FREQ. (f)
SEP0402EC-R10M-LF	0.10 $\pm$ 20%	12.0	12.0	4.1	4.5	100KHz/0.25V
SEP0402EC-R22M-LF	0.22 $\pm$ 20%	9.00	9.00	6.5	7.0	100KHz/0.25V
SEP0402EC-R47M-LF	0.47 $\pm$ 20%	7.00	7.00	14.5	16.0	100KHz/0.25V
SEP0402EC-1R0M-LF	1.0 $\pm$ 20%	5.00	4.50	24.0	27.0	100KHz/0.25V
SEP0402EC-2R2M-LF	2.2 $\pm$ 20%	3.25	3.25	61.0	68.0	100KHz/0.25V
SEP0402EC-4R7M-LF	4.7 $\pm$ 20%	1.75	1.70	95.0	105.0	100KHz/0.25V

- I sat : DC current at which the inductance drops 20% (typ) from its value without current.
- I rms : Average current for a 40°C temperature rise above 25°C ambient.
- Operating temperature range -55°C to +125°C , Electrical specifications at 25°C.

PACKAGING SPECIFICATION



STAYLE	Q' TY (PCS)	DIMENSIONS (m/m)					
		Ao	Bo	Ko	P	Po	D $\pm$ 0.3
13"	2,000	4.5 $\pm$ 0.1	5.5 $\pm$ 0.1	2.3 $\pm$ 0.1	12	4.0	12