

SEP0502EB SERIES

High Current SMD Power Inductors



RoHS Compliant

PART NUMBERING SYSTEM


SEP	0502EB	—	4R7M	—	LF
TYPE	DIMENSIONS		INDUCTANCE		LEAD FREE

FEATURES :

- Low profile (2.0mm max. height) and 5.75 mm max. square.
- Magnetically shielded and low DC resistance and Suitable for large current .
- Ultra low buzz noise, due to composite construction .
- Ideal for DC – DC converter inductor application in hand help personal Computer ,etc .
- Frequency range up to 5MHZ .
- Large current handling capability .

SHAPES AND DIMENSIONS :


UNIT : mm



A=5.75 Max. B=5.45 Max. C=2.5±0.3 D=2.0 Max. E=1.0±0.3

RECOMMENDED PATTERNS

UNIT : mm



H=2.8 G= 2.16 I = 6.0

SEP0502EB SERIES

High Current SMD Power Inductors



RoHS Compliant

SPECIFICATION TABLE

PART NUMBER	INDUCTANCE (μ H)	Isat (A) (Typ.)	Irms (A) (Typ.)	DCR (m Ω) (Typ.)	DCR (m Ω) (Max.)
SEP0502EB-R10M-LF	0.10 $\pm$ 20%	45.0	17.0	3.60	3.90
SEP0502EB-R22M-LF	0.22 $\pm$ 20%	22.0	15.0	4.90	5.20
SEP0502EB-R33M-LF	0.33 $\pm$ 20%	25.0	12.0	7.60	8.20
SEP0502EB-R47M-LF	0.47 $\pm$ 20%	21.0	11.5	8.90	9.40
SEP0502EB-R68M-LF	0.68 $\pm$ 20%	15.0	10.0	11.2	12.4
SEP0502EB-1R0M-LF	1.0 $\pm$ 20%	16.0	7.00	18.9	20.0
SEP0502EB-2R2M-LF	2.2 $\pm$ 20%	12.5	4.20	45.6	50.1
SEP0502EB-3R3M-LF	3.3 $\pm$ 20%	8.50	3.30	79.2	85.5
SEP0502EB-4R7M-LF	4.7 $\pm$ 20%	5.00	2.80	108	116.6
SEP0502EB-5R6M-LF	5.6 $\pm$ 20%	4.50	2.50	113	122.0
SEP0502EB-6R8M-LF	6.8 $\pm$ 20%	4.30	2.40	139	150.0
SEP0502EB-100M-LF	10 $\pm$ 20%	4.00	2.30	184	199.0

- I sat : DC current at which the inductance drops 20% (typ) from its value without current.
- I rms : Average current for a 40°C temperature rise above 25°C ambient.
- Test Frequency at 100KHz / 0.1V
- Operating temperature range -55°C to +125°C , Electrical specifications at 25°C .